

Industry, Energy and Technology

**AIRBORNE GEOPHYSICAL SURVEY OF THE
BURIN PENINSULA REGION, NEWFOUNDLAND**

**NTS MAP AREAS
1M/06, 1M/07, 1M/10 AND 1M/11**

FIRST VERTICAL DERIVATIVE OF THE MAGNETIC FIELD

**MAP 2022-04
OPEN FILE NFD/3402
Map 4 of 26**

G.J. Kilfoil

ABOUT THE SURVEY

Introduction
This qualitative gamma-ray spectrometric, aeromagnetic and VLF-EM airborne geophysical survey of Burin Peninsula region, Newfoundland, was completed by Sander Geophysics Limited. The survey was flown from November 12th 2021 to March 29th, 2022 using a single Cessna 282 Caravan (C-GSGW). The nominal reverse and control line spacings were, respectively, 150 m and 1000 m, and the aircraft flew at a nominal terrain clearance of 50 m at an airspeed between 200 and 270 km/h. Traverse lines were oriented 135° with orthogonal control lines. The flight path was recovered following post-flight differential GPS corrections using raw data recorded by Global Positioning Systems in the survey aircraft and a static reference station.

Gamma-ray Spectrometric Data
The airborne gamma-ray measurements were made with a Sander Geophysics SGL-Spec gamma-ray spectrometer using Mean 1024x1024x40 mm NaI (TI) crystals. The main detector array consisted of twelve crystals (total volume 55.4 litres). Three crystals (total volume 12.6 litres), shielded by the main array, were used to detect variations in background radiation caused by atmospheric radon. The system continuously adjusted the gain of each crystal by monitoring the natural potassium, uranium, and thorium peaks. A small cesium source was used to supplement the responses of the three natural peaks for the upward-looking crystals.

Potassium is measured directly from the 1460 keV gamma-ray photons emitted by ⁴⁰K, whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products (²¹⁴Pb for uranium and ²¹⁴Pb for thorium). Although these daughters are far down their respective decay chains, they are assumed to be in equilibrium with their parents, thus gamma-ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e. eU and eTh. The energy windows used to measure potassium, uranium and thorium are, respectively, 1570-1570 keV, 1660-1860 keV and 2410-2810 keV.

Gamma-ray spectra were recorded at one-second intervals. Data processing followed standard procedures as described in IEA, 1991 and IEA, 2003. During processing, the spectra were energy calibrated, and counts were accumulated into the windows described above. Counts from the radon detectors were recorded in a 1660-1860 keV window and radiation at energies greater than 3000 keV was recorded in the cosmic window. The window counts were corrected for background activity from cosmic radiation, radioactivity of the aircraft and atmospheric radon decay products. This window data were then corrected for spectral scattering in the ground, air and detectors. Corrections for deviations from the planned terrain clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over the Breckenridge, Quebec calibration range. Corrected data were interpolated to a 30 m grid interval. The results of an airborne gamma-ray spectrometer survey represent the average surface concentrations that are influenced by varying amounts of surface, overburden, vegetation cover, soil moisture and surface water. As a result, the measured concentrations are usually lower than the actual bedrock concentrations. The total air absorbed dose rate in mR/hour was determined from measured counts, having energies between 450 and 2810 keV.

Magnetic Data
The magnetic field was sampled 10 times per second using three split-beam cesium vapour magnetometers (sensitivity = 0.005 nT) mounted inside the tail boom and two wingtip pods of the aircraft. This array of sensors form a horizontal gradiometer with a lateral dimension of 19.20 m and a longitudinal dimension of 9.95 m. Differences in magnetic values at the intersections of control and traverse lines were computer-analysed to obtain a mutually derived high-line magnetic data. The International Geomagnetic Reference Field (IGRF) defined at the average GPS altitude of 249 m for the date January 1st 2022 was then removed. Removal of the IGRF, representing the magnetic field of the Earth's core, yields a residual component related essentially to magnetizations within the Earth's crust. An enhanced version of the leveled magnetic data was calculated by leveraging lateral and longitudinal gradients to better define short wavelength signals, which was then interpolated to a 30 m grid interval.

The first vertical derivative of the magnetic field is the rate of change of the magnetic field in the vertical direction. Computation of the first vertical derivative removes long wavelength features of the magnetic field and significantly improves the resolution of closely spaced and superposed anomalies. A property of the first vertical derivative map is the coincidence of the zero-value contour with vertical contacts of magnetic units at high magnetic latitudes (Frost, 1965).

VLF-EM
Very low frequency (VLF) electro-magnetic data was measured using a Herz Totem 2A VLF-EM receiver mounted in a 2.5 m fibreglass stinger towed behind the aircraft. For the survey, combinations of Line and Ortho data from the VLF stations in Cuper, Maine (24.6 kHz), L'Anse-au-Loup, North Dakota (25.2 kHz) and Skekton, UK (24.1 kHz) provide complete coverage of the survey area for both Total and Quadrature representations of the VLF signal. Variation in signal quality from the different stations is apparent in the data as bands of more or less coherent data.

Additional Information
Data compilation and map production were performed by Sander Geophysics Limited, Ottawa, Ontario. Contact and project management was provided by the Newfoundland and Labrador Department of Industry, Energy and Technology. Geomatics Canada, Natural Resources Canada. Government of Newfoundland and Labrador, PO Box 8700, St. John's, N.S., Canada, A1B 4J9.


This map is subject to revision and modification. Comments to the author concerning errors or omissions are invited.
Department Website: <https://www.gov.nl.ca/iel>
Geological Survey website: <https://www.gov.nl.ca/iel/mines/>
E-mail: pub@sgl.com

Reference
1965. Gradient measurements in aeromagnetic surveying. Geophysics, vol. 30, p. 891-902.

PLANIMETRIC SYMBOLS

Topographic contours.....	
Drainage.....	
Road.....	
Flight line.....	
Buildings.....	
Transmission line.....	

NATIONAL TOPOGRAPHIC SYSTEM REFERENCE AND GEOPHYSICAL MAP INDEX



Recommended Citation
Kilfoil, G.J.
2022. Airborne Geophysical Survey of the Burin Peninsula region, Newfoundland (NTS Map Areas 1M/06, 1M/07, 1M/10 and 1M/11). First Vertical Derivative of the Magnetic Field. Geological Survey, Department of Industry, Energy and Technology, Government of Newfoundland and Labrador, Map 2022-04, Open File NFD/3402.

Note
Open File reports and maps issued by the Geological Survey, Division of the Newfoundland and Labrador Department of Industry, Energy and Technology are made available for public use without being formally edited or peer reviewed. They are based upon preliminary data and evaluation. The purchaser agrees not to provide digital reproduction or copy of this product to a third party. Derivative products should acknowledge the source of the data.

Disclaimer
The Geological Survey, a division of the Newfoundland and Labrador Department of Industry, Energy and Technology (the 'authors and publishers'), retains the sole right to the original data and information found in any product produced. The authors and publishers assume no legal liability or responsibility for any misstatements, changes or misrepresentations made by third parties with respect to these products or for derivative products made by third parties. Please consult with the Geological Survey to ensure originality and correctness of data and/or products.