



NOTES:

1. THIS DETAIL IS INTENDED TO SHOW TYPICAL DIMENSIONS FOR PAYMENT PURPOSES ONLY. ACTUAL TRENCH DIMENSIONS ARE SUBJECT TO FIELD CONDITIONS AND/OR THE REQUIREMENTS OF THE HEALTH AND SAFETY REGULATIONS.
2. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE NOTED.
3. BEDDING TYPE SHALL BE AS SPECIFIED IN THE CONTRACT DOCUMENTS REQUIRED SCHEDULE OF QUANTITIES AND PRICES.
4. BUILDING SERVICES ARE TO TERMINATE AT THE SAME POINT AT THE EDGE OF THE ROAD RIGHT OF WAY. A 38 x 89 WOODEN MARKER POST SHALL BE INSTALLED PLUMB FROM THE END OF THE SERVICE LINES TO 600mm ABOVE THE GROUND SURFACE, PAINTED RED ABOVE THE GROUND. WHEN FACING THE BUILDING TO BE SERVICED, THE WATER SERVICE SHALL BE LOCATED ON THE RIGHT OF THE STORM SEWER, AND THE SANITARY TO THE LEFT OF THE STORM SEWER.
5. LOCATION, ALIGNMENT AND ELEVATION OF SERVICE LINES, SHALL BE CONFIRMED BY CONTRACTOR WITH ENGINEER PRIOR TO CONSTRUCTION.
6. WHEN STORM SERVICE IS NOT REQUIRED, MAINTAIN A MINIMUM 300mm HORIZONTAL SEPARATION BETWEEN WATER AND SANITARY SERVICES.

**MUNICIPAL MASTER
SPECIFICATIONS**

**TYPICAL TRENCH DETAIL
BUILDING SERVICE LINES**

DRAWING NUMBER 04050

DATE: APRIL 2023
SCALE: N.T.S.